

NEW ISE/NEW ISK/NEW ISM



Impianto di aspirazione liquidi - Fluids drainage system - Installation d'aspiration de liquides
Absaugstation für Flüssigkeiten - Instalación de aspiración de líquidos


NEW ISE



NEW ISK



NEW ISM



Per motocicli
For motorcycles
Pour les motos
Für Motorräder
Para motos

-  Acqua Tergi (Solo ISE/ISK) - Windscreen-wiper water (Only ISE/ISK)
Eau essuie-glace (Seulement ISE/ISK) - Scheibenwasser (Nur ISE/ISK)
Agua de limpiaparabrisas (Solamente ISE/ISK)
-  Olio freni - Brakes oil - Huile des freins
Bremsflüssigkeit - Aceite de frenos
-  Acqua radiatore/antigelo Radiator's water - Eau radiator
Kühlflüssigkeit - Agua del radiador
-  Olio Trasmissione/Idroguida - Gear box oil - Huile transmission
Getriebeöl - Aceite de transmisión
-  Olio differenziale - Differential gear oil - Huile différentiel
Differenzialöl - Aceite de diferencial
-  Olio cambio - Gearbox oil - Huile boîte de vitesses
Getriebeöl - Aceite de transmisión
-  Olio motore - Engine oil - Huile motor
Motoröl - Aceite de motor
-  Benzina (Solo ISM) - Petrol (Only ISM) - Essence (Seulement ISM)
Benzin (Nur ISM) - Gasolina (Solamente ISM)

IT

Isola di bonifica formata da pompe a depressione pneumatiche ognuna specifica per liquido prelevato.

EN

Fluid Drainage Air system composed by vacuum pumps for each single fluid.

FR

Ilot d'assainissement composé de pompes à dépression; chaque spécifique pour le liquide soutiré.

DE

Absaugstation, mit pneumatischen Pumpen, für jede Flüssigkeit eine spezifische Pumpe

ES

Unidad de recuperación compuesta de bombas de depresión neumática, cada una específica para el líquido recogido.



UNI EN ISO 9001:2015
ref. N° 50 100 12164

La tecnologia del nuovo ambiente
New ELV Recycling Technology
La technologie du nouveau environnement
Technologie für unsere Umwelt
A tecnologia do novo ambiente

NEW ISE / NEW ISK			ASPIRAZIONE / SUCTION / ASPIRATION / SAUGLEISTUNG/ ASPIRACIÓN
		Olio motore - Engine oil drainage - Huile motor - Motoröl - Aceite del motor	50 l/min - 11 UK gal/min Pompa pneumatica Air pump Pompe pneumatique Druckluftpumpe Bomba de air
		Olio freni - Brakes oil - Huile des freins - Bremsflüssigkeit - Aceite de frenos	
		Olio trasmissione / idroguida - Gear box oil drainage - Huile transmission - Getriebeöl - Aceite de la caja de cambios	
		Acqua radiatore / antigelo - Radiator's water - Eau radiator - Kühlfüssigkeit - Agua del radiator	
		Acqua tergi - Windscreen-wiper water - Eau essuie-glace - Scheibenwasser - Agua del limpiaparabrisas	
		Olio cambio - Gearbox oil - Huile boîte de vitesses - Getriebeöl - Aceite de transmisión	
		Olio differenziale - Differential gear oil - Huile différentiel - Differenzialöl - Aceite de diferencial	
			PRESTAZIONI / PERFORMANCES / PERFORMANCE / LEISTUNGEN / PRESTACIONES
		N° cidi lav./Ora - N° cycle-hour - N° cycles du travail-heure - Arbeitszyklen pro Stunde - Ciclos/hora	6 / 10
		Pressione max - Max working pressure - Pression max - Max. Druck - Presión máxima	6 Bar
		Portata max - Max flow - Débit max - Max. Luftdurchfluss - Capacidad máxima	50 l/min - 11 UK gal/min
		Comandi pneumatici - Pneumatic console - Tableau de bord pneumatique - Bedienpult Pneumatisch - Cuadro de Mando Neumático	
		Cisterne esterne controllate da processore- External tanks driven by a processor - Cisterne esterne poussé par un processeur Externe Tanks Angetrieben von einem -Prozessor - Tanque externo Controlado por procesador	
		CARATTERISTICHE TECNICHE / TECHNICAL FEATURES / CARACTÉRISTIQUES TECHNIQUES / TECHNISCHE MERKMALE / CARACTERÍSTICAS TÉCNICAS	
		Peso - Weight - Poids - Gewicht - Peso	280 kg - 618Lbs
		Dimensioni - Overall dimensions - Dimension - Abmessungen - Dimensión total	990 x 650 mm h. 1350 mm 39 x 26 in h. 54 in

NEW ISM			ASPIRAZIONE / SUCTION / ASPIRATION / SAUGLEISTUNG/ ASPIRACIÓN
		Olio motore - Engine oil drainage - Huile motor - Motoröl - Aceite del motor	50 l/min - 11 UK gal/min Pompa pneumatica Air pump Pompe pneumatique Druckluftpumpe Bomba de air
		Olio freni - Brakes oil - Huile des freins - Bremsflüssigkeit - Aceite de frenos	
		Olio trasmissione / idroguida - Gear box oil drainage - Huile transmission - Getriebeöl - Aceite de la caja de cambios	
		Acqua radiatore / antigelo - Radiator's water - Eau radiator - Kühlfüssigkeit - Agua del radiator	
		Olio cambio - Gearbox oil - Huile boîte de vitesses - Getriebeöl - Aceite de transmisión	
		Olio differenziale - Differential gear oil - Huile différentiel - Differenzialöl - Aceite de diferencial	
		Benzina - Petrol - Essence - Benzin - Gasolina	
			PRESTAZIONI / PERFORMANCES / PERFORMANCE / LEISTUNGEN / PRESTACIONES
		N° cidi lav./Ora - N° cycle-hour - N° cycles du travail-heure - Arbeitszyklen pro Stunde - Ciclos/hora	6 / 10
		Pressione max - Max working pressure - Pression max - Max. Druck - Presión máxima	6 Bar
		Portata max - Max flow - Débit max - Max. Luftdurchfluss - Capacidad máxima	50 l/min - 11 UK gal/min
		Comandi pneumatici - Pneumatic console - Tableau de bord pneumatique - Bedienpult Pneumatisch - Cuadro de Mando Neumático	
		Cisterne esterne controllate da processore- External tanks driven by a processor - Cisterne esterne poussé par un processeur Externe Tanks Angetrieben von einem -Prozessor - Tanque externo Controlado por procesador	
		CARATTERISTICHE TECNICHE / TECHNICAL FEATURES / CARACTÉRISTIQUES TECHNIQUES / TECHNISCHE MERKMALE / CARACTERÍSTICAS TÉCNICAS	
		Peso - Weight - Poids - Gewicht - Peso	280 kg - 618 Lbs
		Dimensioni - Overall dimensions - Dimension - Abmessungen - Dimensión total	1500 x 1600 x h 1800 mm 60 x 63 h 71 in



UNI EN ISO 9001:2015
ref. N° 50 100 12164

Rev: 05/11/2021

La tecnologia del nuovo ambiente
New ELV Recycling Technology
La technologie du nouveau environnement
Technologie für unsere Umwelt
A tecnologia do novo ambiente